



Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

vredo.com

## ART.NUMBER

## DETAILS

C001092

VREDO PROFI 9.0M DS H

Vredo Profi 9.0 DS H

- Machinenumber: 1020.033
- Year of construction: 2020
- Discs: 33cm
- Section control
- 3-point

Specifications:

- Working width 9,0 meter
- Inter row distance 18,75 cm
- Vredo single V-disc system
- 48 discs
- Mechanic and suspended duo elements, free of maintenance
- Duo elements are mounted with torsion rubbers to be able to rotate/steer in a small angle
- Cassette seals and double row ball bearings for disc bearings
- Easy to replace wear parts: discs, scraper blocks and steel turf guards
- Hydraulic dropstop
- Open constructed folding frame made out of 3 parts
- Automatic (hydraulic and mechanic) transport safety
- Automatic mechanic operated reflecting disc cover set for safe transport on the road
- 1 connection for central greasing of hinge points
- Frame has the possibility to lever in a free way thanks to the fact the hydraulic cylinders of in- and out folding are connected with each other by help of a parallelogram construction
- Parallelogram lever construction is locked in case hydraulic function of folding in is operated (adjustable for headland management)
- Leveling and unlevelling by way of adjusting the length of a special bar in the parallelogram construction
- Meets the requirements of the road transport legislation for the Netherlands and Germany
- Rear marking
- Registration plate holder incl. lightning
- 1x Vogelsang Dosimat DMX 50-40-800 distributor
- Slurry hoses 40mm, for precise distribution
- Stainless steel hose clamps on slurry hoses and rubber slurry outlets
- Transport width bottom: 2,98 m
- Transport width top: 2,48 m
- Height standing on the bottom: 3,80 m
- Assumed weight ca. 2630kg
- LED lightning
- Platform and foldable access steps for Vogelsang distributor
- Demountable counterpart of A-frame

Required connections:

- 2x 1/2" In/out folding (open center)
- 2x 1/2" dropstop (closed center)
- 2x 3/4" distributor (open center), distributor needs a continuous oil flow of 60L/min
- 1x 1/2" pressureless return line
- 6" KKV slurry hose connection
- 1x connection for central greasing supplied by vehicle

OPT. HYDR SECT. CTRL I/O 6 SECTIONS

I/O controlled sectioncontrol for Profi 7.5m/8.25m/9.0m DV H and Profi 7.5m/8.25m/9.0m DS H (Hydraulic DropStop)

Standard equipped with:

- 16 pin plug and cable
- 7.5m = controllable in 6 sections. (4\*1.5m / 2\* 0.75m)
- 8.25m = controllable in 6 sections. (4\*1.5m / 2\* 1.125m)
- 9.0m = controllable in 6 sections. (6\*1.5m)
- In combination with Vredo Trac, controlled from VTC (or via linkage Trimble/VTC)

# Vredo

Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

[vredo.com](http://vredo.com)

