



Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

**Your fields,
our passion**

vredo.com

ART.NUMBER

DETAILS

C001099

ZB3 8750

Vredo ZB3 8750

- Machinenummer: 1121.036
- Year of construction: 2009
- Discs: 38.5 cm

Specifications:

- Working width 8,7 meter
- Inter row distance 17.5 cm
- Vredo double disc system (spoke discs)
- SKF Central bearing lubrication and lubrication of other hinge points by automatic grease device fitted on slurry injector.
- Lubrication reservoir 4L
- Needed for power supply: 1 electrical connection point 12V 15A on vehicle
- Automatically hydraulic shutter set of the slurry outlets
- 3 sections-frame with automatic locking for safe road transport
- Device for positioning distributor in horizontal position
- Easy to replace wear-resistant HPME slide blocks
- Stainless steel hose clips on the slurry hoses and the rubber slurry outlets
- Transportation width 2,85 meter
- Weight ±3110 kg
- Automatic reflecting disc cover for safe transport
- LED lightning kit
- A-frame quick connection
- Special angular-contact bearings as disc bearings
- 6" KKV (male) Slurry hose connection on top of distributor

Required hydraulics:

- 3x Double acting (2x open center, 1x closed center), The distributor needs a continuous oil flow of 55L/min
- 1x pressure less return line

Connections:

- 2x 1/2" In/out folding
- 2x 1/2" closing rubber drop stop outlets
- 2x 3/4" distributor
- 1x 1/2" pressure less return line

Attention: When towed machine is without closed center function please choose option 1100o070-01



Vredo

Vredo Dodewaard bv
Welysestraat 25a
6669 DJ Dodewaard (NL)
Tel. +31(0)488411254
info@vredo.com

Your fields,
our passion

vredo.com

